





MIBLE MIXING STATIONS

TwinMix 1800/TwinMix 1800 T





The mobile stations for thorough mixing





Specifications	TWINMIX 1800/1800 T
Power input	1800 W
Rated voltage	230 V ~
Rated speed mixing rod	250/450 rpm
Rated speed mixing paddle	20/36 rpm
Bucket size	65 l
Spindle connection	M 14/Special
Weight	70.0 kg
Order no.	07621000/07623000
Supplied on a pallet incl. mixing and transport carriage	g rod, mixing paddle, bucket 65 l

USE:

- Homogenous and lump free mixing of numerous materials with different viscosity
- Especially convenient for the mixing of self-levelling floor levelling compounds, plaster, thin-bed mortar, fillers
- Building construction and civil engineering, landscaping, floor renovators, tilers

FEATURES:

- Mixing paddle with scraper avoids material deposits on the bucket rim and ensures together with a fast running inner rod a better mixing
- Two electronic speed levels start mixing function with reduced speed
- Transport carriage with handles and big wheels mobile use of the station at the construction sites, also at rough terrain





- Delivery in largely completed condition immediately ready to use
- Robust universal motor very high pulling power
- Electronic soft start, constant speed, temperature control and overload cut-off
- Switch with dust protection and protection against re-start
- Safety Switch cut-off in case of opening the hood, protection of the operator
- Connection for dust exhaust Ø 35 mm as well as funnel tube with brushes – dust reduced filling and mixing of the materials
- Tipper (accessory) especially designed for clean and precise pouring of self-levelling filler and levelling compounds
- Mixing carriage (supplied) can be used separate from the station – flexible and mobile at the job site

Accessories	Order no.
Timer for TwinMix 1800 T	32352000
Mixing paddle	31451000
Scraper for mixing paddle	32351000
Universal stirring rod	31452000
Transport carriage	09Z11000
Tipper	09Z12000
Bucket 65 l	32341000









Versatile application possibilities – best mixing results



masonry mortar



thin-bed mortar



plaster



floating screed



tilo comon



arout



insulation board adhesive



screed



fillor

Fast, uninterrupted work when using several mixing carriages, f. e. for levelling filler




- ⇒ saves time and costs
- reduces the risk that the material is setting too fast in wet-on-wet cycle

(10:15



(10:20











Timer for TwinMix 1800 T for setting the requested mixing time for special requirements of the material manufacturer (accessory)





Reduction of hazardous dusts

- cleanliness in the interior



Hazardous dust (e.g. silica dust) has to be suctioned by a Dust Class M Vacuum Cleaner! For our electric power tools we are recommending to use a Vacuum Cleaner of our Eibenstock DSS range!















Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 08309 Eibenstock, Germany

Phone: +49 (0) 3 77 52 - 50 30 +49 (0) 3 77 52 - 20 19 Fax: Internet: www.eibenstock.com office@eibenstock.com E-Mail:

Certified according to DIN EN ISO 9001:2015 Technical changes excepted! Illustrations may vary! Your distributor:

19293000 - Stand 01/17