



EIBENSTOCK
Elektrowerkzeuge

PROFESSIONAL
GERMAN SINCE 1919
POWER TOOLS



**SMOOTHING OF PLASTER
AND SANDING OF PANELS**



Plaster smoothing machines EPG 400 and EPG 400 WP



The versatile plaster smoothing machines

Until now



saves at least
50 % time

Smoothing, scraping and structuring of plaster, sanding of panels for heat insulations, smoothing and cleaning of surfaces

Large tool surface – smooth and quick working

Low weight – for effortless work

Vertical arrangement of motor, large handles – balanced, ergonomic design, convenient working

Electronic switch – stepless speed control

Triple special gearbox – high torque, powerful, durable


EPG 400 WP additionally with: Stepless adjustable water supply – direct moistening of the wall by means of an atomised spray, saves adding water separately, thus time saving



Sponge disc

Sponge rubber disc

Smoothing disc



Scratching disc



Scraping disc



Felt disc



Sanding disc

Specifications	EPG 400	EPG 400 WP
Power input	500 W	500 W
Rated voltage	230 V~	230 V~
Rated speed	0-60 rpm	0-60 rpm
No-load speed	110 rpm	110 rpm
Base plate	370 mm	370 mm
Spindle connection	Push fit fitting/velcro	Push fit fitting/velcro
Weight	3.5 kg	3.8 kg
Order no.	06509000	0650L000
Supplied	in a case incl. base plate and sponge disc	

We recommend as accessories:
EIBENSTOCK water tank





Insulation board sander **EWS 400**

The insulation board sander for large surfaces

Until now



saves at least
50 % time

**Sanding of foamed polystyrene
and mineral insulation panels for
heat insulations**



Dust extraction by hood with brush rim and perforated sanding disc – emission of sanding dust and particles is effectively removed, saves time-consuming cleaning of the construction site

Flexible hood – gets close to the surface

Dust extraction – connection of the industrial vacuum cleaner

Large tool surface – smooth and quick working

Vertical arrangement of motor, large handles – balanced, ergonomic design, convenient working

Electronic switch – stepless speed control

Triple special gearbox – high torque, powerful, durable

Specifications	EWS 400
Power input	800 W
Rated voltage	230 V~
Rated speed	0-85 rpm
No-load speed	140 rpm
Base plate	370 mm
Spindle connection	Push fit fitting/velcro
Weight	3.9 kg
Order no.	0620F000
Supplied	in a box incl. 1x sandpaper P24

Hazardous dust (e. g. silica dust) has to be suctioned by a Dust Class M Vacuum Cleaner! For our electric power tools we are recommending to use a Vacuum Cleaner of our Eibenstock DSS range!





Accessories



	EPG 400	EPG 400 WP	EWS 400	
1 Sandpaper (velcro), 4 hole punch, P24 (3 pieces)			•	37671000
2 Base plate Ø 370 mm	•	•		37721000
3 Sponge disc Ø 400 mm (velcro)	•	•		37722000
4 Sponge rubber disc Ø 385 mm (velcro)	•	•		37725000
5 Scraping disc Ø 380 mm (velcro)	•	•		37726000
6 Sanding disc P24, Ø 370 mm (velcro)	•	•		37727000
7 Smoothing disc Ø 380 mm	•	•		37728000
8 Felt disc Ø 395 mm	•	•		37729000
9 Scratching disc Ø 370 mm	•	•		37724000
10 Add on kit for scratching disc (set of 5 scratching metal sheets + 10 screws)	•	•		37723000
11 Water tank, 5 l plastic		•		35811000
12 Water tank, 10 l metal		•		35812000



Hazardous dust (e. g. silica dust) has to be suctioned by a Dust Class M Vacuum Cleaner! For our electric power tools we are recommending to use a Vacuum Cleaner of our Eibenstock DSS range!

Specifications	DSS 25 M	DSS 35 M iP
Max. power input	1400 W	1600 W
Rated voltage	230 V~	230 V~
Tank volume	25 l (brutto)	35 l (brutto)
Dust volume	20 l (netto)	25 l (netto)
Max. air flow	61 l/s	64 l/s
Max. vacuum	248 mbar	259 mbar
Weight	12.7 kg	15.0 kg
Order no.	09917000	09919000
Supplied	in a box incl. accessories	in a box incl. accessories

Elektrowerkzeuge GmbH Eibenstock
 Auersbergstraße 10
 08309 Eibenstock, Germany

Phone: +49 (0) 3 77 52 - 50 30
 Fax: +49 (0) 3 77 52 - 20 19
 Internet: www.eibenstock.com
 E-Mail: office@eibenstock.com

Certified according to DIN EN ISO 9001:2015
 Technical changes excepted! Illustrations may vary!

Your distributor: