









The compact and powerful entry level

USE:

- Fixing of construction boards (e.g. plasterboards) on metal and wood frames as well other assembly work

FEATURES:

- Powerful motor clean and quick countersink of screws up to Ø 5 mm
- Speed control, acceleration function, reversible
- Electronic switch with lock for continuous use
- Gearbox with internal gear teeth durable
- Detachable depth gauge with notch stops
- Automatic switch off when reaching the screw depth
- Soft handle, belt clip

Handy, light but still extremely powerful

USE:

- Fixing of construction boards (e.g. plasterboards) on metal and wood frames as well other assembly work

FEATURES:

- Powerful motor clean and quick countersink of screws up to Ø 5 mm
- Speed control, acceleration function, reversible
- Electronic switch with lock for continuous use
- Gearbox with internal gear teeth durable
- Detachable depth gauge with notch stops
- Automatic switch off when reaching the screw depth
- Quiet claw clutch, belt clip
- Light: weight only 1.1 kg, overall length: 250 mm, handle circumference 175 mm

SPECIFICATIONS	ESR 450
Power input	450 W
Rated voltage	230 V ~
No-load speed	0-4000 rpm
Srews in wood	Ø 5 mm
Corner accessibility	33.0 mm
Collar diameter	-
Spindle connection	1/4"
Weight	1.2 kg
Order no.	06102000
Supplied	in a box incl. depth gauge

SPECIFICATIONS	ESR 500
Power input	500 W
Rated voltage	230 V ~
No-load speed	0-4650 rpm
Srews in wood	Ø 5 mm
Corner accessibility	22.5 mm
Collar diameter	43 mm
Spindle connection	1/4"
Weight	1.1 kg
Order no.	06101000
Supplied	in a box incl. depth gauge, size 2 PH bit and magnetic bit holder







Chiselling hammer EMH 650





The chiselling hammer for comfortable use

USE:

- Chipping of tiles, plaster, chiselling of core and drill bits and the finishing of slots
- Ideal for the refurbishment and renovation industries, e.g. tilers and electricians

FEATURES:

- Powerful chisel
- Cut-off carbon brushes protect the motor
- Selector wheel for variable impact frequency
- Low speed start for accurate and soft chiselling
- High impact, powerful motor, low weight
- Ergonomically designed front no need for a front handle allowing easy overhead use

SPECIFICATIONS	EMH 650
Power input	650 W
Rated voltage	230 V ~
No-load impact rate	0-3200 rpm
Impact energy	4.2 J
Spindle connection	SDS-plus
Weight	3.4 kg
Order no.	02511000
Supplied	in a case incl. pointed, flat and tile chisel





FOR HAND-HELD DRILLING MACHINES					
	1			09507000	
1		for EHB 32/2.2 R R/L and EHB 32/4.2			
	2	Weldon mounting shank			
		MT 3 - Ø 19 mm		33125000	
3		Taper mandrel			
		B 16/MT 2		33111000	
		B 18/MT 2		33112000	
		B 18/MT 3		33122000	
4	4	Quick action drill chuck			
		½" x 20	Ø 13 mm	33433000	
		B 16	Ø 13 mm	33431000	
		B 16	Ø 16 mm	33441000	
		%" x 16 UN	Ø 16 mm	33444000	
5	5	Scroll chuck			
		B 18	Ø 16 mm	33342000	
		M 18	Ø 16 mm	33345000	
	6	Reducing sleeve			
		MT 3 - MT 2		33621000	
	7	Adapter			
		MT 2 male - M 14 female		33113000	
		MT 3 male - M 14 female		33123000	
8		Drill chuck key 13 33520000			
4	4		13		
		16		33540000	
1	9	Plastic case 37332000 for EHB 16, EHB 20/2.4			

FOR DRY-WALL SCREWDRIVER ESR 500



Collated screws for collating adapter no. 37701000

magazined, PH 2, fine thread 1000 screws in a box (strips of screws - 50 screws each)

3.9 x 35 mm 3.9 x 25 mm 37712000 37713000