Diamond Core Drilling

ESD 16/2.4 I

Diamond Dry Core Drill Machine









- → Dry drilling up to 90 mm for particularly hard materials, e.g. highly compressed limestone, reinforced concrete and other abrasive materials with a high working speed
- → Producing of wall and roof openings for sanitary, heating and ventilation installations
- → For electrical installation work socket sinking e.g. switches and sockets

Features:

- → Powerful motor
- → Electronic soft start
- → Gearbox with switchable soft percussion high working speed
- → Mechanical safety clutch
- → Additional handle variable adjustment on the collar

SPECIFICATION	ESD 16/2.4 I
Input Watts (W)	1100
Voltage (V)	220 - 240
Rated Speed (n) min-1	0-1100 / 0-2050
Spindle Connection	M16
Mechanical Safety Clutch	YES
Drilling Capacity in brickwork (mm)	Ø 162
Drilling Capacity in hard Concrete (mm)	up to Ø 90
Weight (kg)	3.7

Eibenstock Positron Elektrowerk Pvt. Ltd. Plot No. 144/1,2,3, KATP, Tardal, Taluka- Hatkanangale, Dist. Kolhapur – 416 121, Maharashtra, (INDIA)

GERMAN ENGINEERING



A partner company of The German Power Tool

