Metal Core Drilling with Swivel Base

KDS 100.1 S



KDS 100.1 S 220-240

1800

50/60

100

110

2 speed 60-140 / 200-470

31.75

31.75

50

Up to M30

126

MT3

19 & 32 mm Weldon

Yes

Yes

Yes

Yes

220 x 126.5 x 65.5

720 (Max.)

35.2





Specification

Max. Core Cutting Capacity Ø (mm)

Max. Core Cutting Depth (mm)

Rated Speed (RPM) n

Twist Drill Ø (mm)

Countersunk (mm)

Tapping Capacity

Stroke (mm)

Morse Taper

Direct Arbor

Torque control

Safety clutch

Swivel Base

Height (mm)

Weight (kg)

Overheating protection

Magnetic Base size (L x B x H) mm

Reaming (mm)

Input Supply Voltage (V) Motor Output (Watt)

Frequency (Hz)

Speed

Use :

- Electrical installation, sanitary and heating installations, Vehicle Construction.
- Civil engineering, industrialised building construction & Heavy fabrication

Features:

- Mechanical safety clutch
- → Easy feed lever change
- Line lock out
- Safety Belt
- Powerful motor
- Superb service life
- Powerful electromagnet
- Epoxy sealed waterproof base
- Internal spindle cooling system
- Soft Start and Thermal over load for the protection of the machine & user (EHB 32/2.2 R R/L)
- Constant speed and torque control allows for precise drilling (EHB 32/2.2 R R/L)
- Safety fuse protection for magnet
- → 100% high tensile alien headed screws
- Un-mistaken arrangement of switch for magnet & drill to ensure safety of operator

as per your requirement

 Tapping attachment, Tapping Collet, Pipe Clamping Attachment & Core Bits are Optional accessory

* Tapping attachment, Tapping Collet, & Core Bit is not a part of standard accessory

Eibenstock Positron Elektrowerk Pvt. Ltd. Plot No. 144/1,2,3, KATP, Tardal, Taluka- Hatkanangale, Dist. Kolhapur – 416 121, Maharashtra, (INDIA)

GERMAN ENGINEERING

ষ্টিভ ন্থল **হ্বঁভি**ন্দা www.eibenstock.in www.facebook.com/EibenstockPositron A partner company of The German Power Tool Manufacturer

