



Standard Accessories



Core Bits



Tapping attachment,  
Tapping Collet

### Use :

- ➔ Electrical installation, sanitary and heating installations, Vehicle Construction.
- ➔ Civil engineering, industrialised building construction & Heavy fabrication

### Features ::

- ➔ Mechanical safety clutch
- ➔ Easy feed lever change
- ➔ Line lock out
- ➔ Safety Belt
- ➔ Powerful motor
- ➔ Superb service life
- ➔ Powerful electromagnet
- ➔ Epoxy sealed waterproof base
- ➔ Internal spindle cooling system
- ➔ Soft start and thermal over load for the protection of the machine & user (EHB 130/2.2 R R/L)
- ➔ Constant speed and torque control allows for precise drilling (EHB 130/2.2 R R/L)
- ➔ Safety fuse protection for magnet
- ➔ 100% high tensile alien headed screws
- ➔ Tapping attachment, Tapping Collet, & Core Bits are Optional accessory as per your requirement

Specification	KBM 130
Input Supply Voltage (V)	220-240
Motor Input (W)	2300
Max Core Cutting Capacity (mm)	* Core drill short 30mm : 12 to 130 mm * Core drill long 55 mm : 12 to 100 mm * Core drill extra long 110mm : 20 to 120 mm
Max Core Cutting Depth (mm)	110
Rated Speed (RPM)	* 30 to 85 min - 1 * 50 to 135 min - 1 * 130 to 390 min - 1 * 210 to 620 min - 1
Weight (kg)	50
Tapping Capacity	up to M42 mm
Electro Torque control	Yes
Thermal Overload Protection	Yes
* Twist drilling : Capacity (Max)	O 45mm
* Reaming : (Max)	O 50mm
* Morse taper	MT 4
* Direct arbor :	32 mm Weldon

**\* Tapping attachment, Tapping Collet,  
& Core Bit is not a part of standard accessory**