





PLD 182/PLE 182 – powerful and compact for hardest applications in series drilling up to Ø 182 mm

EIBENSTOCK Elektrowerkzeuge

PROFESSIONAL GERMAN SINCE 1919

Optimized efficiency with special gearbox adjustment for powerful drilling progress



USE:

- Wet drilling in reinforced concrete, natural stone and asphalt
- Drilling operators, civil engineering, sanitary, heating and ventilation construction, other installation companies, garden- and landscaping trade

FEATURES:

- Robust full-aluminium-housing
- Shortest design in its power range ideal for narrow spaces

Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 08309 Eibenstock, Germany

Phone:	+49 (0) 3 77 52 - 50 30
Fax:	+49 (0) 3 77 52 - 20 19
Internet:	www.eibenstock.com
E-Mail:	office@eibenstock.com

Certified according to DIN EN ISO 9001:2015 Technical changes excepted! Illustrations may vary!

- Powerful 2300 W motor with high power reserves and a long lifetime, able for continuous work under pressure
- Electronic soft start, over current cut-off, overload indication
- 3-speed oil bath gearbox for optimal lubrication in all working positions due to the specially developed oil pump and optimal adjusted torque-speed-ratio for all diameters
- Mechanical safety clutch
- Ergonomic handle with large-dimensioned switch button
 good control and effortless working
- PUR-construction site cable strong for heavy duty use
- Integrated levels on machine and on the carriage, scale and hole center indicator on the drill rig – exact drilling
- Collar mounting variable machine position in the rig
- Column of the rig can be adjusted to 45°
- Compact combination base fixing with anchor or vacuum (vacuum set necessary)
- Feed lever change without any tools easy change of the working site
- Retrofitable wheel axle (accessory) easy transport

Specifications	PLD 182
Power input	2300 W
Rated voltage	230 V ~
Rated speed	0-520/0-1250/0-2700 rpm
No-load speed	950/2200/4400 rpm
Drilling diameter	1. Gear 82-182 mm 2. Gear 42-82 mm 3. Gear 12-42 mm
Collar diameter	60 mm
Spindle connection	G½" female + 1¼" male
Weight	7.5 kg
Order no.	0343P000
Supplied	in a case incl. jaw wrench SW 32 + 41
Specifications	PLE 182
Column length	995 mm
Hub	700 mm
Weight	21.5 kg
Order no.	0343S000
Supplied without drill bit	PLD 182 + BST 182 V/S + connecting adapter

Your distributor: